



# 1812 RESIDENTIAL TELEPHONE INTERCOM SYSTEM



surface mount



flush mount



wall mount



### talk

to your front door or gate from any telephone in your home!



### control access

with a simple push of a button on your touch-tone telephone



### full-duplex

Hi quality communication – the same standard that the phone company uses



### three styles

to choose from; surface, wall or flush mount designs

- Unique communication and access control system that allows homeowners to use their telephone as an intercom to speak to a guest at a front door or gate
- System connects directly to the homeowners existing telephone line. No additional monthly expenses for a separate telephone line for the access system
- Calls from the access system are identified with a double ring while regular calls use the standard single long ring. Homeowners know instantly if a call is coming from their door or gate
- Homeowners grant their guest access by pressing 9 on their telephone, or they can deny access by simply hanging up
- Built-in call waiting feature assures that incoming calls or guest calls are not missed
- Windows compatible auto-programming software allows homeowners to program the system from their PC
- 2-year limited warranty

FEATURES










## ACCESS CONTROL SOLUTIONS





# 1812 RESIDENTIAL TELEPHONE INTERCOM SYSTEM

is a unique communication and access control device that provides homeowners with two-way voice communication, and control of a door or gate, through their existing telephone. Visitors are easily identified by voice communication and can be granted or denied access directly from any telephone in the home. The Windows compatible auto-programming software, and the many advanced features of the 1812, allow the homeowner complete control of their access system.



## 1812 Surface

10" W x 6.25" H x 5.25" D  
254mm W x 159mm H x 133mm D

## 1812 Flush

12" W x 9.25" H x 4.5" D  
305mm W x 235mm H x 112mm D

## 1812 Wall

10.75" W x 7.325" H x 3.5" D  
273mm W x 186mm H x 88.9mm D

## 1812 Specs

### Communication

True full duplex  
Hands free

### Styles

Surface mount - indoor or outdoor applications  
Flush mount - indoor or outdoor applications  
Wall mount - indoor or outdoor applications

### Capacity

Single line  
Two relays allow control of two doors or gates

### Programming Methods

System keypad  
Touch-tone telephone  
Auto program software

### Advanced Features

Call waiting  
Call forwarding  
Three (3) preprogrammed call out phone numbers  
Unique ring  
Multiple systems may share same phone line  
Built-in clock/calendar  
Do not disturb time zone  
Four (4) hold-open time zones  
50 4-digit entry codes  
Entry code time zones  
Call forwarding time zone  
Flash entry code  
Special intercom mode for use with PBX and KSU phone systems  
Slave keypad can be added for entry code access at a second door or gate  
Camera Ready:  
Optional B&W or Color CCTV camera\* can be added to the 1812

\*may require additional CCTV equipment

### Operating Temp

10°F to 145°F  
-12°C to 62°C  
Optional heater kit available for colder climates

### Electrical Requirements

24 VAC, 20 VA, 250ma  
UL listed power transformer provided

### Safety Standards

FCC (US) DUF6VT-12874-OT-0  
DOC (CAN) 1736 4507 A  
Complies with UL 294  
ETL Listed

### Shipping Weight

Approximately 15 lbs (7 kg)

### Warranty


2 year limited factory warranty

## DOORKING, INC.

120 Glasgow Avenue, Inglewood, California 90301 U.S.A. Tel: 310-645-0023 FAX: 310-641-1586 www.doorking.com

© 2007 All Rights Reserved. Product specifications may change without notice. Rev. 4/07

## MEMBER:



Distributed by:  
**Calvin Access Controls Inc.**  
740-494-4200 or 614-451-GATE  
[sales@CALVINInc.com](mailto:sales@CALVINInc.com)  
[www.CALVINInc.com](http://www.CALVINInc.com)